



GO BEYOND™

M-7 / M-9 Mainsails

Quick Tuning Chart

06/2018 Update/NS Japan



BASE SETTING	
MAST RAKE	6110 ± 10 mm
PRE-BEND	50 - 55 mm
SIDE TENSION	31 - 31.5 by Loose PT-1 gauge (to be measured with chocks) with 2.5mm 1X7 hard wire
MAST STEP	2820 - 2830mm (from back end of the mast groove to back end of the boat)

		1-9 KNOTS	10-16 KNOTS	16-20 KNOTS	20+ KNOTS
SHROUDS PIN POSITION		1	2	3	4
MAST RAKE		6110 ± 10 mm	6070 ± 10 mm	6030 ± 15 mm	5990 ± 15 mm
PRE-BEND		45 - 55 mm			55 - 65 mm
WEDGE (5mm from neutral)	M-7	0 - 0.5	1 - 2	1 - 2	0.5 - 1.5
	M-9	0 - 0.5	0.5 - 1.5	0.5 - 1.5	0 - 1
JIB TACK POSITION		Wrinkles	Smooth	Tight	Very tight
OUTHHAUL (from the band) w/ 10 mm space at the tack	M-7	25 mm			15 mm
	M-9	10 - 15 mm		5 - 15 mm	0 - 10 mm

* The thickness of one wedge is 5mm